



**ZEETAH**

**捷泰橡膠工業股份有限公司**

【堆 高 機 系 列 】

2012.12/25



| 實心胎規格      | RIM            | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|------------|----------------|-------------|-------------|--------------|---------------------|
| 3.50-5     | 2.75/3.00      | 292         | 100         | 5.5          | 500                 |
| 4.00-8     | 2.50/3.00/3.75 | 405         | 105         | 11           | 720                 |
| 15×4 1/2-8 | 3.00           | 381         | 115         | 10           | 850                 |
| 16×5-8     | 3.75           | 406         | 125         | 14           | 950                 |
| 16×6-8     | 4.33           | 415         | 148         | 15.5         | 1100                |
| 5.00-8     | 3.00           | 455         | 125         | 16.5         | 1100                |
| 18×7-8     | 4.33           | 455         | 170         | 22           | 1650                |
| 6.00-9     | 4.00           | 540         | 150         | 28           | 1450                |
| 21×8-9     | 6.00           | 525         | 190         | 35           | 2200                |
| 140/55-9   | 4.00           | 380         | 135         | 10.5         | 1000                |
| 400-10     | 2.75           | 410         | 100         | 8.5          | 850                 |
| 6.50-10    | 5.00           | 575         | 162         | 35.5         | 1800                |
| 200/50-10  | 6.50           | 460         | 205         | 24.5         | 1800                |
| 23×9-10    | 6.50           | 580         | 220         | 49           | 2700                |
| 4.50-12    | 3.00           | 535         | 115         | 18           | 1250                |
| 7.00-12    | 5.00           | 667         | 170         | 48           | 2400                |
| 8.25-12    | 5.00           | 714         | 188         | 60.5         | 3400                |
| 23×7-12    | 5.00           | 560         | 174         | 29.5         | 1900                |
| 23×10-12   | 8.00           | 580         | 245         | 50           | 2800                |
| 27×10-12   | 8.00           | 675         | 245         | 74           | 3500                |
| 27×6.5-15  | 5.50           | 665         | 180         | 42.5         | 2500                |
| 5.50-15    | 4.50           | 665         | 155         | 36           | 1900                |
| 6.00-15    | 4.50           | 665         | 155         | 36           | 1900                |
| 7.00-15    | 5.50/6.00      | 740         | 178         | 61           | 2800                |
| 7.50-15    | 5.50/6.00      | 800         | 184         | 75           | 3400                |
| 8.15-15    | 7.00           | 710         | 211         | 62           | 3000                |
| 250-15     | 7.00/7.50      | 710         | 238         | 71           | 3600                |
| 8.25-15    | 6.50           | 820         | 206         | 89           | 4200                |
| 300-15     | 8.00           | 820         | 260         | 110          | 5000                |
| 28×12.5-15 | 9.75           | 718         | 310         | 94.5         | 4800                |
| 32×12.5-15 | 9.75           | 820         | 300         | 130          | 5400                |
| 355/65-15  | 9.75           | 840         | 360         | 157          | 5800                |
| 7.50-16    | 5.50/6.00      | 800         | 184         | 73           | 3400                |
| 8.25-16    | 6.00           | 845         | 212         | 95           | 3800                |
| 9.00-16    | 7.00           | 845         | 237         | 107.5        | 4500                |
| 26×8-16    | 6.00           | 650         | 175         | 43           | 2700                |
| 28×9-16    | 6.00           | 717         | 210         | 56           | 3000                |
| 8.25-20    | 6.50           | 980         | 220         | 125          | 4800                |
| 9.00-20    | 7.00           | 980         | 220         | 125          | 4800                |
| 10.00-20   | 7.00/7.50/8.00 | 1040        | 250         | 166          | 5500                |



【堆 高 機 系 列 】

2012.12/25

PATTERN 601



| 實心胎規格        | RIM            | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|--------------|----------------|-------------|-------------|--------------|---------------------|
| 11.00-20 SU  | 7.00/7.50/8.00 | 1040        | 250         | 166          | 5500                |
| 11.00-20 SUW | 7.50           | 1040        | 275         | 185          | 6000                |
| 11.00-20     | 7.50/8.00/8.50 | 1110        | 265         | 211          | 6500                |
| 12.00-20     | 7.50/8.00/8.50 | 1110        | 265         | 211          | 6500                |
| 12.00-20     | 8.50           | 1040        | 305         | 203          | 7000                |
| 12.00-20     | 8.00/8.50      | 1140        | 295         | 248          | 7000                |
| 380/70-20    | 12.00          | 1040        | 385         | 265          | 9000                |
| 14.00-20     | 10.00          | 1140        | 335         | 287          | 9000                |
| 14.00-20     | 10.00          | 1250        | 350         | 380          | 10000               |
| 12.00-24     | 8.00/8.50      | 1210        | 304         | 264          | 7500                |
| 13.00-24     | 8.50           | 1250        | 320         | 315          | 8600                |
| 14.00-24     | 10.00          | 1320        | 340         | 386          | 10000               |
| 14.00-25     | 10.00/11.25    | 1320        | 340         | 386          | 10000               |
| 16.00-25     | 11.25          | 1500        | 410         | 635          | 12500               |
| 18.00-25     | 13.00          | 開發中         |             |              |                     |
|              |                |             |             |              |                     |



【堆 高 機 系 列 】

2012.12/25

PATTERN 601 Non-marking



| 實心胎規格      | RIM       | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|------------|-----------|-------------|-------------|--------------|---------------------|
| 15×4 1/2-8 | 3.00      | 381         | 115         | 10           | 850                 |
| 16×6-8     | 4.33      | 415         | 148         | 15.5         | 1100                |
| 5.00-8     | 3.00      | 455         | 125         | 16.5         | 1100                |
| 18×7-8     | 4.33      | 455         | 170         | 22           | 1650                |
| 6.00-9     | 4.00      | 540         | 150         | 28           | 1450                |
| 21×8-9     | 6.00      | 525         | 190         | 35           | 2200                |
| 140/55-9   | 4.00      | 380         | 135         | 10.5         | 1000                |
| 6.50-10    | 5.00      | 575         | 162         | 35.5         | 1800                |
| 200/50-10  | 6.50      | 460         | 205         | 24.5         | 1800                |
| 23×9-10    | 6.50      | 580         | 220         | 49           | 2700                |
| 7.00-12    | 5.00      | 667         | 170         | 48           | 2400                |
| 23×10-12   | 8.00      | 580         | 245         | 50           | 2800                |
| 27×10-12   | 8.00      | 675         | 245         | 74           | 3500                |
| 8.15-15    | 7.00      | 710         | 211         | 62           | 3000                |
| 250-15     | 7.00/7.50 | 710         | 238         | 71           | 3600                |
| 8.25-15    | 6.50      | 820         | 206         | 89           | 4200                |
| 300-15     | 8.00      | 820         | 260         | 110          | 5000                |
|            |           |             |             |              |                     |
|            |           |             |             |              |                     |

PATTERN 601 Click



| 實心胎規格      | RIM       | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|------------|-----------|-------------|-------------|--------------|---------------------|
| 15×4 1/2-8 | 3.00      | 381         | 115         | 10           | 850                 |
| 16×6-8     | 4.33      | 415         | 148         | 15.5         | 1100                |
| 5.00-8     | 3.00      | 455         | 125         | 16.5         | 1100                |
| 18×7-8     | 4.33      | 455         | 170         | 22           | 1650                |
| 6.00-9     | 4.00      | 540         | 150         | 28           | 1450                |
| 21×8-9     | 6.00      | 525         | 190         | 35           | 2200                |
| 140/55-9   | 4.00      | 380         | 135         | 10.5         | 1000                |
| 6.50-10    | 5.00      | 575         | 162         | 35.5         | 1800                |
| 200/50-10  | 6.50      | 460         | 205         | 24.5         | 1800                |
| 23×9-10    | 6.50      | 580         | 220         | 49           | 2700                |
| 7.00-12    | 5.00      | 667         | 170         | 48           | 2400                |
| 23×10-12   | 8.00      | 580         | 245         | 50           | 2800                |
| 27×10-12   | 8.00      | 675         | 245         | 74           | 3500                |
| 7.00-15    | 5.50/6.00 | 740         | 178         | 61           | 2800                |
| 7.50-15    | 5.50/6.00 | 800         | 184         | 75           | 3400                |
| 8.15-15    | 7.00      | 710         | 211         | 62           | 3000                |
| 250-15     | 7.00/7.50 | 710         | 238         | 71           | 3600                |
| 8.25-15    | 6.50      | 820         | 206         | 89           | 4200                |
| 300-15     | 8.00      | 820         | 260         | 110          | 5000                |



【堆高機系列】

2012.12/25

PATTERN 601H



| 實心胎規格       | RIM            | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|-------------|----------------|-------------|-------------|--------------|---------------------|
| 5.00-8      | 3.00           | 457         | 120         | 15.5         | 990                 |
| 6.00-9      | 4.00           | 540         | 150         | 27.5         | 1300                |
| 6.50-10     | 5.00           | 575         | 160         | 34.5         | 1620                |
| 7.00-12     | 5.00           | 667         | 170         | 48           | 2160                |
| 8.15-15     | 7.00           | 710         | 210         | 61           | 2700                |
| 250-15      | 7.00/7.50      | 710         | 238         | 70.5         | 3240                |
| 8.25-15     | 6.50           | 845         | 212         | 96           | 3780                |
| 300-15      | 8.00           | 840         | 280         | 116          | 4500                |
| 8.25-20     | 6.50           | 980         | 220         | 123          | 4320                |
| 9.00-20     | 7.00           | 980         | 220         | 123          | 4320                |
| 10.00-20    | 7.00/7.50/8.00 | 1040        | 250         | 163          | 4950                |
| 11.00-20 SU | 7.00/7.50/8.00 | 1040        | 250         | 163          | 4950                |
| 11.00-20    | 7.50/8.00/8.50 | 1110        | 265         | 208          | 5850                |
| 12.00-20    | 8.00/8.50      | 1140        | 295         | 245          | 6300                |
|             |                |             |             |              |                     |
|             |                |             |             |              |                     |
|             |                |             |             |              |                     |
|             |                |             |             |              |                     |
|             |                |             |             |              |                     |

PATTERN 602



| 實心胎規格      | RIM       | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|------------|-----------|-------------|-------------|--------------|---------------------|
| 15×4 1/2-8 | 3.00      | 380         | 115         | 9.5          | 850                 |
| 16×6-8     | 4.33      | 411         | 150         | 15.5         | 1100                |
| 5.00-8     | 3.00      | 457         | 130         | 17.5         | 1100                |
| 18×7-8     | 4.33      | 457         | 165         | 21.5         | 1650                |
| 6.00-9     | 4.00      | 520         | 158         | 27.5         | 1450                |
| 21×8-9     | 6.00      | 528         | 190         | 34.5         | 2200                |
| 6.50-10    | 5.00      | 583         | 166         | 38           | 1800                |
| 200/50-10  | 6.50      | 462         | 195         | 24           | 1800                |
| 23×9-10    | 6.50      | 588         | 210         | 49           | 2700                |
| 7.00-12    | 5.00      | 660         | 170         | 48           | 2400                |
| 23×10-12   | 8.00      | 588         | 240         | 51           | 2800                |
| 27×10-12   | 8.00      | 685         | 240         | 76           | 3500                |
| 8.15-15    | 7.00      | 710         | 212         | 63           | 3000                |
| 250-15     | 7.00/7.50 | 751         | 240         | 79.5         | 3600                |
| 8.25-15    | 6.50      | 832         | 210         | 93           | 4200                |
| 300-15     | 8.00      | 832         | 265         | 117          | 5000                |
|            |           |             |             |              |                     |
|            |           |             |             |              |                     |
|            |           |             |             |              |                     |



【堆高機系列】

2012.12/25

PATTERN 701



| 實心胎規格   | RIM  | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|---------|------|-------------|-------------|--------------|---------------------|
| 6.00-9  | 4.00 | 540         | 150         | 28.5         | 1450                |
| 7.00-12 | 5.00 | 667         | 172         | 48.5         | 2400                |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |
|         |      |             |             |              |                     |

PATTERN 702



| 實心胎規格           | RIM       | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|-----------------|-----------|-------------|-------------|--------------|---------------------|
| 5.00-8          | 3.00      | 463         | 120         | 16.5         | 1100                |
| 18×5.5-8        | 3.50/4.33 | 457         | 140         | 19           | 1200                |
| 6.00-9          | 4.00      | 540         | 163         | 29.5         | 1450                |
| 6.50-10         | 5.00      | 580         | 172         | 37.5         | 1800                |
| 17 1/2×6-10     | 5.00      | 452         | 150         | 16.5         | 1400                |
| 200/50-10       | 6.50      | 452         | 195         | 23.5         | 1800                |
| 7.00-12         | 5.00      | 660         | 182         | 48.5         | 2400                |
| 8.15-15         | 7.00      | 717         | 210         | 60.5         | 3000                |
| 22 1/4×7 1/2-15 | 5.50      | 580         | 172         | 26.5         | 2100                |
|                 |           |             |             |              |                     |
|                 |           |             |             |              |                     |
|                 |           |             |             |              |                     |

PATTERN 704



| 實心胎規格   | RIM            | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|---------|----------------|-------------|-------------|--------------|---------------------|
| 13×4-5  | 2.75           | 314         | 96          | 5.5          | 500                 |
| 3.50-5  | 2.75/3.00      | 328         | 90          | 6.5          | 500                 |
| 4.00-8  | 2.50/3.00/3.75 | 406         | 108         | 11.5         | 720                 |
| 4.80-8  | 3.00/3.75      | 406         | 115         | 12.8         | 900                 |
| 15×4-8  | 3.00           | 378         | 91          | 6.5          | 760                 |
| 16×5-9  | 3.50           | 406         | 125         | 12           | 1000                |
| 16×5-12 | 3.75           | 406         | 124         | 7.5          | 780                 |
| 6.00-20 | 4.50           | 850         | 160         | 60           | 3000                |
|         |                |             |             |              |                     |
|         |                |             |             |              |                     |
|         |                |             |             |              |                     |
|         |                |             |             |              |                     |

**2012.12/25**

[illegible][illegible]

**2012.12/25**

| 實心胎規格    | RIM   | O.D.<br>m/m | S.W.<br>m/m | WEIGHT<br>KG | CAPACITY<br>25 Km/H |
|----------|-------|-------------|-------------|--------------|---------------------|
| 7.50-16  | 6.00  | 805         | 194         | 71           | 2600                |
| 8.25-16  | 6.00  | 845         | 212         | 94           | 3300                |
| 30×10-16 | 6.00  | 767         | 240         | 75           | 2200                |
| 33×12-16 | 8.00  | 845         | 275         | 110          | 3200                |
| 13.00-24 | 8.50  | 1250        | 320         | 310          | 6800                |
| 14.00-24 | 10.00 | 1320        | 340         | 377          | 8000                |
| 50×16-24 | 11.50 | 1250        | 400         | 388          | 8000                |
| 16.00-25 | 11.25 | 1500        | 410         | 600          | 10000               |
| 17.5-25  | 14.00 | 1340        | 440         | 510          | 8500                |
| 20.5-25  | 17.00 | 1480        | 520         | 765          | 9600                |
| 23.5-25  | 19.50 | 1610        | 590         | 1042         | 10500               |
| 26.5-25  | 22.00 | 1720        | 650         | 1345         | 14500               |
| 29.5-25  | 25.00 | 1870        | 740         | 1855         | 18500               |
| 35/65-33 | 28.00 | 2030        | 850         | 2360         | 24000               |
| 18.00-33 | 13.00 | 開發中         |             |              |                     |
| 21.00-35 | 15.00 | 開發中         |             |              |                     |
| 24.00-35 | 17.00 | 開發中         |             |              |                     |
|          |       |             |             |              |                     |
|          |       |             |             |              |                     |

[illegible]

**2012.12/25**

[illegible]

**2012.12/25**

[illegible][illegible]

**2012.12/25**

## PATTERN 801H

A 3D rendering of a heavy-duty tire, likely for a bulldozer, featuring a deep, aggressive tread pattern with large, blocky lugs. The tire is shown from a side-on perspective, highlighting its robust construction and the 'PATTERN 801H' branding on the sidewall.[illegible]

## 【大包膠胎（礦產車）系列】

## PATTERN 601



A 3D rendering of a heavy-duty tire, labeled 'PATTERN 601'. The tire features a black tread with deep, aggressive sipes and a wide, flat top surface. The rim is a bright orange color with a complex, multi-spoke design. The tire is shown from a three-quarter perspective, highlighting its robust construction and tread pattern.

[illegible]